

## STATEMENT OF WORK

### Work to be done:

Offerors are required to provide items as described below. All items must be new, off the shelf, officially imported and guaranteed.

The offerors shall provide not less than a one-year warranty with ability to fix items locally in Ukraine together with information on the availability of authorized service centers for the performance of warranty and post-warranty repair (including maintenance) of equipment, required within this SOW, with its location(s) and telephone numbers.

**Delivery and Deadline:** Requested items should be delivered to the U. S Embassy Kyiv within 60-90 days after the contract award. The offer must include the costs of the products and delivery to the final destinations.

**Voltage, frequency and plug requirements:** All devices must be compatible with standard Ukrainian voltage (220-230 volts), support 50 Hz current frequency and have C (European) or F (Schuko) plug type.

**Xerox Altalink C8135, color MFP with office finisher (brand name or equal)**

### Quantity – 3

#### Salient Characteristics:

Speed (Color/Black-and-White): Up to 35/35 or better

Monthly Duty Cycle: Up to 110,000 pages or more

Hard Drive/Processor/Memory: Minimum 160 GB SSD; 1.9GHz/4 GB system memory

The network connectivity will not be used and prefer that it be physically removed, but if not it must have the capability to disable it especially the WiFi/NC.

Copy Resolution: 600 x 600 dpi or better

Print Resolution: 1200 x 2400 dpi or better

First-Copy-Out Time (as fast as)(from platen/warmed-up state): at least 6 seconds color/4 seconds black-and-white

First-Print-Out Time (as fast as): 5.70 seconds color/4.20 seconds black-and-white

Page Description Languages: Adobe® PostScript® 3™, Adobe® PDF, PCL® 5c/PCL® 6

#### Paper Input:

Single-Pass Duplex Automatic Document Feeder (DADF): Up to 82 ppm simplex/141 ipm duplex (200 dpi). 130-sheet capacity or more

Paper sizes: 3.4 x 4.9 in. to 11.7 x 17 in./85 x 125 mm to 297 x 432 mm.

Bypass Tray: at least 100 sheets; Custom sizes: 3.5 x 3.9 to 12.6 x 52 in./89 x 98 mm to 320 x 1,320 mm

Tray 1: at least 500 sheets; Custom sizes: 5.5 x 7.2 in. to 11.7 x 17 in./140 x 182 mm to 297 x 432 mm

Tray 2: at least 500 sheets; Custom sizes: 5.5 x 7.2 in. to 12 x 18 in./140 x 182 mm to SRA3

High-Capacity Tandem Tray Module: at least 2,000 sheets; Sizes: 8.5 x 11 in./A4. Total standard paper capacity: at least 3,000 sheets

**Paper Output:**

**Dual Offset Catch Tray** (standard when finishers are not attached): at least 250 sheets each; Face-up Tray: at least 100 sheets

**Office Finisher:**

Output capacity - 2000 sheets or more

Paper size - from 210 x 182 mm to 297 x 432 mm

Paper weight - 52–300 g/sqm

Multi-positional stapling, minimum 50 sheets (90 g/sqm<sup>2</sup> or less)

**Additional features:**

Scan Preview

**ADDITIONAL REQUIREMENTS:**

Encrypted Hard Disk (AES 256-bit, FIPS 140-2) with Image Overwrite

Removable hard drive

The possibility to disable all wireless technology (Wi-Fi, Bluetooth, ...etc.) either physically or administratively

Document Security Under Evaluation Common Criteria Certification (ISO 15408) full system against the HCP PP, Encrypted Secure Print, FIPS 140-2 Encrypted Data with Print Drivers

**Xerox Altalink B8145, Monochrome MFP with Finisher (brand name or equal)**

**Quantity – 11**

**Salient Characteristics:**

Speed (Color/Black-and-White): Up to 45 ppm or better

Monthly Duty Cycle: Up to 200,000 pages

Hard Drive/Processor/Memory: Minimum 160 GB SSD; 1.9GHz/4 GB system memory

The network connectivity will not be used and prefer that it be physically removed, but if not, it must have the capability to disable it especially the WiFi/NC.

Copy Resolution: 600 x 600 dpi or better

Print Resolution: 1200 x 2400 dpi or better

First-Copy-Out Time (as fast as) (from platen/warmed-up state): 4.40 seconds

First-Print-Out Time (as fast as): 3.80 seconds

Page Description Languages: Adobe® PostScript® 3™, Adobe® PDF, PCL® 5c/PCL® 6

**Paper Input:**

Single-Pass Duplex Automatic Document Feeder (DADF): Up to 82 ppm simplex/141 ipm duplex (200 dpi). 130-sheet capacity or more

Paper sizes: 3.4 x 4.9 in. to 11.7 x 17 in./85 x 125 mm to 297 x 432 mm.

Bypass Tray: at least 100 sheets; Custom sizes: 3.5 x 3.9 to 12.6 x 52 in./89 x 98 mm to 320 x 1,320 mm

Tray 1: at least 500 sheets; Custom sizes: 5.5 x 7.2 in. to 11.7 x 17 in./140 x 182 mm to 297 x 432 mm

Tray 2: at least 500 sheets; Custom sizes: 5.5 x 7.2 in. to 12 x 18 in./140 x 182 mm to SRA3

High-Capacity Tandem Tray Module: at least 2,000 sheets; Sizes: 8.5 x 11 in./A4. Total standard paper capacity: at least 3,000 sheets

**Paper Output:**

Dual Offset Catch Tray (standard when finishers are not attached): at least 250 sheets each; Face-up Tray: 100 sheets or more

**Office Finisher:**

Output capacity - 2000 sheets or more

Paper size - from 210 x 182 mm to 297 x 432 mm

Paper weight - 52–300 g/sqm

Multi-positional stapling, minimum 50 sheets (90 g/sqm<sup>2</sup> or less)

**Additional features:**

Scan Preview

**ADDITIONAL REQUIREMENTS:**

Encrypted Hard Disk (AES 256-bit, FIPS 140-2) with Image Overwrite

Removable hard drive

The possibility to disable all wireless technology (Wi-Fi, Bluetooth, ...etc.) either physically or administratively

Document Security Under Evaluation Common Criteria Certification (ISO 15408) full system against the HCP PP, Encrypted Secure Print, FIPS 140-2 Encrypted Data with Print Drivers